

10/599225

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 October 2005 (06.10.2005)


PCT

(10) International Publication Number  
**WO 2005/092677 A1**

- (51) International Patent Classification<sup>7</sup>: **B60R 22/14**, 22/00, B60N 2/28
- (21) International Application Number: PCT/IB2005/000997
- (22) International Filing Date: 22 March 2005 (22.03.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0406829.2 25 March 2004 (25.03.2004) GB
- (71) Applicant (for all designated States except US): **BRITAX ROMER KINDERSICHERHEIT GMBH** [DE/DE]; Blaubeurer Strasse 71, 89077 Ulm (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **WETTER, Hermann** [AT/DE]; Alpenstrasse 60, 89075 Ulm (DE).
- (74) Agent: **NIGEL, BROOKS, CPA**; Hill Hampton, East Meon, Petersfield, Hampshire GU32 1QN (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: SHOULDER PAD FOR VEHICLE SEAT BELT



(57) Abstract: The shoulder pad (30) is positioned on the shoulder strap (24) with the thinner projections (40 and 42) in contact with the shoulder of the child (28) and the thicker projections (46, 48 and 50) in contact with the child's chest. In an initial phase of an accident, the friction provided by these relatively thin projections is insufficient to prevent the child's torso from bending forward, thereby reducing the load on the child's neck. During a subsequent phase of the accident, the thicker projections (46, 48 and 50) reach child's shoulder.

WO 2005/092677 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*